

## DHI-KTA04

#### Video Intercom KIT





- · Video intercom function: Unlock, voice call, video call, volume adjustment and doorway monitoring
- Multiple bell sounds
- Support digital wide dynamic range (DWDR)













Technical Specification	Technical	<b>Specificati</b>	on
-------------------------	-----------	--------------------	----

#### DHI-VTH1010J

Gross Weight

0.42 kg (0.96 lb)

#### DHI-VTO1000J

#### System

Button Type	Mechanical
Basic	
Camera	1.3 MP CMOS
Field of View	Horizontal: 70° Vertical: 40°
WDR	DWDR
Illuminator Type	Auto IR
Day/Night	ICR auto switch
Audio Input	1 channel to the microphone; pickup distance 0.5 m
Audio Output	1 channel to the speaker
Status Indicator	1 indicator light Green: Power on
Function	
Communication Method	Analog
Unlock Mode	Remote unlock
Performance	
Casing	PC + ABS
Port	
Exit Button	1
Door Status Detection	1
General	
Color	Silver
Power Supply	Powered by indoor monitor
Installation	Surface mount

### Video Intercom KIT | DHI-KTA04


Certifications	CE/FCC
Accessory	Rain cover (included)
Dimensions	131.45 mm × 46.00 mm × 33.80 mm (5.18" × 1.81" × 1.33")
Protection Grade	IP66 (Apply silicon sealant to gaps between the device and the wall. Liquid sodium silicate is recommended. For details, see the quick start guide.)
Operating Temperature	−30 °C to +60 °C (−22 °F to +140 °F)
Operating Humidity	10%–95% (RH)
Power Consumption	≤ 1 W (standby) ≤ 3 W (working)
Net Weight	0.18 kg (0.40 lb)
Gross Weight	0.38 kg (0.84 lb)

DHI-VTO1000	46.0 [1.81]	33.8 [1.33] 33.0 [1.30] 29.5 [1.16]	

# Ordering Information Type Model Description Video Intercom Kit DHI-KTA04 Video Intercom Kit

#### Dimensions (mm[inch])

DHI-VTH1010J



#### Application

