

# DHI-LM32-S200

## 32" FHD Monitor



### Features :

- Uses tamper-proof metal housing, suitable for continuous 24/7 operation
- 178°H/178°V extra-wide viewing angle for overall viewing performance
- High fidelity digital processing for a brilliant and vivid video
- 6.5ms response time for no motion blur, judder or ghosting
- Support multiple signals, such as HDMI, DVI, VGA, BNC, USB multimedia, Audio, RS232
- Built-in speakers and supports infrared remote control



### Technical Specification

#### Model

Model	DHI-LM32-S200
-------	---------------

#### Display

Screen Size	31.5"
LCD Technology	VA
Aspect Ratio	16:9
Resolution	1920 (H) × 1080 (V)
Backlight	LED
Brightness	400 cd/m <sup>2</sup>
Contrast Ratio	4000:1
Display Color	16.7M (8bit)
Viewing Angle	178° (H)/178° (V)
Response Time	6.5 ms
Refresh Rate	60Hz
Display Mode	Horizontal
Lifespan	30,000 hrs

#### Device Ports

Input Port	2 × CVBS (BNC), 1 × VGA (D-Sub), 1 × DVI-D, 1 × HDMI, 1 × Audio, 1 × RS-232, 1 × USB	
Output Port	2 × CVBS (BNC), 1 × RS-232	
	Speakers	2 × 2 W

### General

Power Supply	100–240 VAC (±10%), 50/60 Hz	
Power Type	Built-in Power	
Power Consumption	35 W (typ.)	
Standby Power Consumption	≤1 W	
Net Weight	10 kg (22.0 lb)	
Gross Weight	11.5 kg (25.4 lb)	
Frame Width	25.5mm (U/L/R/D)	
Wall Mount VESA	300 mm × 300 mm (11.8" × 11.8")	
Product Dimensions	750.7 mm × 455.1 mm × 44 mm (29.6" × 17.9" × 1.7) (L × W × H)	
Package Size	879 mm × 169 mm × 596 mm (34.6" × 6.7" × 23.5") (L × W × H)	
Operating Environment	Temperature	0 °C to 40 °C (32 °F to 104 °F)
	Humidity	10%~85% (RH)

### Accessory

Standard	VGA cable, power cable, remote control
Optional	Base, wall-mount bracket

### Certifications

Certifications	CE/FCC
----------------	--------

Dimensions(mm)

